

P P L X
**STAND-ALONE
PROXIMITY READER**

Entry level access control and security
for small to medium businesses.



KEY FEATURES

- STAND-ALONE**
No need for a Full Access Control System
- EASY TO PROGRAM**

SMART

SYSTEM ALLOWS FOR UP TO 50,000 USERS PROXIMITY CARDS OR KEYFOBS IN MINUTES.

PROGRAMS SIMPLE DELETION OF LOST OR STOLEN CARDS WITHOUT THE NEED TO RE-PROGRAM THE ENTIRE USER SET.




PROGRAMMABLE AS STAND-ALONE OR WIEGAND PASS-THROUGH.

RELIABLE

RUGGED AND DURABLE WEATHERPROOF ENCLOSURE (IP67 RATED), THE PPLX IS SEALED IN A WEATHERPROOF (IP67) ENCLOSURE.

EASILY MOUNTED TO ANY INTERIOR/EXTERIOR SURFACE, OR INSTALLED IN ANY SINGLE GANG ELECTRICAL ENCLOSURE.

TOTAL SOLUTION ACCESSORIES:

| | | |
|--|---|-----------------|
| PROXIMITY RADIO PROGRAMMER Hand-held programmer for use with PPLX. Requires administration code. |  | PPRP |
| PROXCARD II® 1326 CLAMSHELL 26-BIT CARD Proximity card for credentialed access. |  | LMPG2-ST |
| PROXKEY III® 1346 KEYFOB Proximity fob for credentialed access. |  | LMPK3-ST |

MASTERFUL ENGINEERING.

CAPABILITIES



- 50,000 User Capacity
- Programmable Output Relay (NO/NC)
- Multiple Wiegand Protocol (26-Bit Industry Standard, 30-Bit Sentex®)
- "Latch Mode" to Hold the Door or Gate Open
- Timed Anti-Passback Logic

POWER



- 5-14VDC, 150mA (max load)

MECHANICS



- 6" Read Range

DIMENSIONS



- 3.2" W x 4.5" H x 2.0" D

4.5"



3.2"

STANDARD SPECS.

WARRANTY

- 1-Year Limited

INPUT PORTS

- Default is Remote Open (requires contact closure)
- Also programmable as Bicolor (Red or Green) LED Control or Buzzer/LED Control for online systems (see Operating Guide)

OUTPUTS

- SPST Solid-State Relay. 1A max. @60 VAC or DC
- Normally open or normally closed (field programmable)

WIEGAND OUTPUT

- Any Wiegand Format up to 40 bits
- Maximum Distance: 500 ft. – 5 or 6 conductor 20-gauge shielded cable

OPERATING TEMPERATURE -40°F to 158°F
(-40°C to 70°C)

OPERATING HUMIDITY

- 0-90% (non-condensing)

AVAILABLE

ACCESSORIES

| MODEL # | DESCRIPTION |
|----------|---|
| PPRP | Proximity Radio Programmer (Only) |
| PS12D2A | Power Supply 12VDC 2.0A (Only) |
| LMPC2-ST | 26-Bit Proximity Card (Clamshell) (Shipped in sleeves of 100) Only compatible with PPLX in stand-alone mode |

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTON (1)

- Mounting Plate
- Reader
- Cable with Wiring Harness
- Metal Oxide Varistor
- (2) Mounting Screws
- (2) Security Screws
- Log Sheet
- Instruction Manual

For Support Tools and Training Videos, Visit LiftMasterTraining.com

For More Information, Visit LiftMaster.com/AccessControl

Sales Support: **800.282.6225**
 Technical Support Center: **800.528.2806**
LiftMasterDealer.CustHelp.com/App/Ask